

UJALA PUTTELITE - Water Based Putty

Product Data Sheet

DESCRIPTION :

Puttelite is a wall putty. It is based on adhesion-promoted acrylic copolymer, dries quickly, and fills the voids, cracks or other imperfections of wall with good adhesion and hardness. It is easy to apply and can easily smooth up by rubbing with sand paper.

USAGE :

Water based prepared putty for smoothening both exterior and interior wall.

PHYSICAL PROPERTIES :

Form	:	Paste
Binder	:	Acrylic copolymer dispersion
Pigment	:	Titanium dioxide / Mineral extenders
Thinner/Cleaner	:	Water
Colour	:	White
Storage Life	:	8 months in sealed container

DRYING TIMES (at 30° C):

Surface Dry	:	1 hour
Hard dry	:	8 hours
Standing or Overcoating	:	6 hours

SURFACE PREPARATION :

- The surface should be dry, clean and free from any loose or flaking materials
- For New Surface, apply one coat of Alkalite Wall Sealer/WalleliteSU/Aclose Sealer
- For Old Surface, apply one coat of plastelite Wall Sealer/WalleliteSU/Aclose Sealer

APPLICATION METHODS :

It is ready-to-use, However, if necessary thin up to 5% by volume with water. Apply by suitable knife. Allow 6-8 hours to dry before sanding or over-coating. Deep dent should not be filled at a time.

PACK SIZE:

- 25 kg. sealed plastic bucket

CLEANING All equipment should be cleaned with water immediately after use.

- PRODUC** • Emulsion based material, must be protected from frost, heat.
- It is non-flammable under normal conditions of use.
 - Keep away from children

- HEALTH** • Use in good natural ventilation and wear protective clothing
- If splashes enter eyes, wash with plenty of water.
 - Avoid prolonged contact with skin.